

LCW two needle series

High speed, Cylinder bed, Large vertical axis hook, Compound feed and walking foot, Reverse stitch, Lockstitch machines



LCW-28BL

Variety

LCW-28BL

Applications

- For sewing medium to heavy weight fabrics, leather, synthetics, canvas and various coated and laminated materials.
- Suitable for sewing tubular and curved work such as shoes boots, bags and handbags.



LCW two needle series

Features

- Semi-automatic lubrication system.
- Large vertical axis hook.
- Safety clutch prevents the hook from being damaged.
- Reverse stitching by stitch adjusting lever.
- 20 & 30 inches long arm models are available.

Specifications

Variety	LCW-28BL	
Number of needle	Two needle	
Max. sewing speed	1,800 s.p.m.	
Max. stitch length	1/4" (6.2 mm)	
Clearance under presser foot	by pedal	35/64" (14 mm)
	by hand	21/64" (8.5 mm)
Needle bar stroke	1-5/16" (33.2 mm)	
Needle(standard)	DPx17 (#22) , 135x17 (#140)	
Thread	#8 (standard)	
Hook	Large vertical axis hook (2.0times)	
Amount of lift of walking foot	7/64"-7/32" (2.7 - 5.5 mm) standard 1/8" (standard 3.2 mm)	
Thread take up lever	Slide type	
Lubrication	Semi-automatic lubrication type	
Cylinder size	3-7/64"(79 mm) dia.	
Working space	10-5/32" x 4-21/64" (258 x 110 mm)	
Motor	Clutch motor	
Net weight(Head only)	34Kg	

NOTE: (1) Speed depends on threads, materials and type of operation
(2) Specifications subject to change without notice

Needle gauge list

Variety	Needle gauge size
LCW-28BL	Standard : 1/4"(6.4 mm), 5/16"(7.9mm), 3/8"(9.5mm), 1/2"(12.7mm)



SEIKO SEWING MACHINE CO., LTD.

2-13-6, Sakaecho, Funabashi-shi
Chiba Prefecture, 273-0018, Japan

Phone : +81-47-420-3561 (Overseas dept.)

Fax : +81-47-420-3560

E-mail : export@seiko-sewing.co.jp

Printed in Japan 2016.04

<http://www.seiko-sewing.co.jp/>